


LEM Series Red Laser Point Module

Part No: LEM-1022-50xx-SP

Mechanical Drawing



Product Features

High Stability and low noise Collimated or Adjustable focus beam Reverse Polarity Protection Custom Options Available

Application

Measurement Optical Instrument Automation Alignment Point Mark

Specification

I				
OPTICAL				
Wavelength	650 nm			
Optical Output Power ¹	<10mW or < 5 mW or <1mW			
Stability	<1%			
Wavelength Drift	0.2nm/°C			
Noise (20MHz Bandwidth)	<0.5% RMS			
Laser Operation	Continuous			
Laser Structure	Single Mode Laser			
Focus Lens	PMMA Plastic lens			
Beam Divergence	<18mrad			
ELECTRICAL				
Operating Voltage ²	3 or 4.5 VDC			
Operating Current	<40 mA			
Control Circuit	Auto Power Control			
Electrical Connections	+Red, -Black			
MECHANICAL				
Dimension	See chart			
Cable ³	60mm			
Operating Temperature	-10°C to +50°C			
Storage Temperature	-40°C to +80°C			

Notes

- Please advise output power in advance, we can release Class II (under 1mW) or Class IIIa (under 5mW) or Class III (under 10mW) for different market.
- 2. Input power can be fixed in 3 to 5 certain DC voltage.
- 3. Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.
- Caution: The cooper is internally connected to the circuit + pole, wrong connection may damage the laser module.

Model Number Definition:



diameter	total length	wavelength	output	lens	beam	angle
65:6.5mm	20:20mm	50:650nm	01:0.8mW	G:glass	P:point	
80:8.0mm	23:23mm	35:635nm	05:5mW	S:plastic	L:line	1:5°
10:10mm	27:27mm		10:10mW			$2:20^{\circ}$
11:11mm	32:32mm		20:20mW			3:30°
12:11.5mm	35:35mm					$6:60^{\circ}$
						$9:90^{\circ}$
	65:6.5mm 80:8.0mm 10:10mm 11:11mm	diameter total length 65:6.5mm 20:20mm 80:8.0mm 23:23mm 10:10mm 27:27mm 11:11mm 32:32mm 12:11.5mm 35:35mm	65:6.5mm 20:20mm 50:650nm 80:8.0mm 23:23mm 35:635nm 10:10mm 27:27mm 11:11mm 32:32mm	80:8.0mm 23:23mm 35:635nm 05:5mW 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW	65:6.5mm 20:20mm 50:650nm 01:0.8mW G:glass 80:8.0mm 23:23mm 35:635nm 05:5mW S:plastic 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW	65:6.5mm 20:20mm 50:650nm 01:0.8mW G:glass P:point 80:8.0mm 23:23mm 35:635nm 05:5mW S:plastic L:line 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage. **Limited Warranty:** One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.