


LEM Series Red Laser Point Module

Part No: LEM-1127-350x-GP

Mechanical Drawing



Product Features

High Stability and low noise Collimated or Adjustable focus beam Reverse Polarity Protection Custom Options Available

Application

Measurement Optical Instrument Automation Alignment Point Mark

Specification

| OPTICAL | | |
|-----------------------------------|-----------------------|--|
| Wavelength | 635 nm | |
| Optical Output Power ¹ | < 5 mW or <1mW | |
| Stability | <1% | |
| Wavelength Drift | 0.2nm/°C | |
| Noise (20MHz Bandwidth) | <0.5% RMS | |
| Laser Operation | Continuous | |
| Laser Structure | Single Mode Laser | |
| Focus Lens | 3 elements Glass Lens | |
| Beam Divergence | <18mrad | |
| ELECTRICAL | | |
| Operating Voltage ² | 3 or 4.5 VDC | |
| Operating Current | <40 mA | |
| Control Circuit | Auto Power Control | |
| Electrical Connections | +Red, -Black | |
| MECHANICAL | | |
| Dimension | See chart | |
| Cable ³ | 60mm | |
| Operating Temperature | -10ºC to +50°C | |
| Storage Temperature | -40°C to +80°C | |
| | | |

Notes

- 1. Please advise output power in advance, we can release Class II (under 1mW) or Class IIIa (under 5mW) for different market.
- 2. Input power can be fixed in 3 to 5 certain DC voltage.
- 3. Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.
- Caution: The cooper is internally connected to the circuit + pole, wrong connection may damage the laser module.

Model Number Definition:



| T | | | | | | |
|---|-----------|--------------|-------------------|-----------|-----------|----------------|
| | diameter | total length | wavelength output | lens | beam | angle |
| | 65:6.5mm | 20:20mm | 50:650nm 01:0.8m | W G:glass | P:point | |
| | 80:8.0mm | 23:23mm | 35:635nm 05:5mW | ' S:plast | ic L:line | $1:5^{\circ}$ |
| | 10:10mm | 27:27mm | 10:10mW | / | | $2:20^{\circ}$ |
| | 11:11mm | 32:32mm | 20:20mV | V | | $3:30^{\circ}$ |
| | 12:11.5mm | 35:35mm | | | | $6:60^{\circ}$ |
| | | | | | | $9:90^{\circ}$ |

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage. Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.