


# **LEM Series Red Laser Point Module**

Part No: LEM-1132-350x-GP

# **Mechanical Drawing**



#### **Product Features**

High Stability and low noise Collimated or Adjustable focus beam Reverse Polarity Protection Custom Options Available

## **Application**

Measurement
Optical Instrument
Automation
Alignment
Point Mark

### **Specification**

635 nm
< 5 mW or <1mW
<1%
0.2nm/°C
<0.5% RMS
Continuous
Single Mode Laser
3 elements Glass Lens
<18mrad
3 ~ 6 VDC
<40 mA
Auto Power Control
+Red, -Black
See chart
60mm
-10°C to +50°C

#### Notes

- Please advise output power in advance, we can release Class II (under 1mW) or Class IIIa (under 5mW) for different market.
- 2. Output is fixed when Input power from 3 to 6 VDC.
- Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.

Caution: The cooper is internally connected to the circuit + pole, wrong connection may damage the laser module.

#### **Model Number Definition:**

LEM-							
	diameter	total length	wavelength	output	lens	beam	angle
	65:6.5mm	20:20mm	50:650nm	01:0.8mW	G:glass	P:point	
	80:8.0mm	23:23mm	35:635nm	05:5mW	S:plastic	L:line	1:5°
	10:10mm	27:27mm		10:10mW			2:20°
	11:11mm	32:32mm		20:20mW			3:30°
	12:11.5mm	35:35mm					6:60°
							a-an°

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage. Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.