


LEM Series Red Laser Line Module

Part No: LEM-1225-350x-SLx

Mechanical Drawing



Product Features

High Stability and low noise Collimated or Adjustable focus beam Reverse Polarity Protection Custom Options Available

Application

Measurement
Optical Instrument
Automation
Alignment
Line Mark

Specification

OPTICAL			
Wavelength	635 nm		
Optical Output Power ¹	< 5 mW or <1mW		
Stability	<1%		
Wavelength Drift	0.2nm/°C		
Noise (20MHz Bandwidth)	<0.5% RMS		
Laser Operation	Continuous		
Laser Structure	Single Mode Laser		
Focus Lens	PMMA plastic lens		
Line Angle	5°/20°/30°/60°/90°		
ELECTRICAL			
Operating Voltage ²	3 or 4.5 VDC		
Operating Current	<40 mA		
Control Circuit	Auto Power Control		
Electrical Connections	+Red, -Black		
MECHANICAL			
Dimension	See chart		
Cable ³	60mm		
Operating Temperature	-10°C to +50°C		
Storage Temperature	-40°C to +80°C		

Notes

- Please advise output power in advance, we can release Class II (under 1mW) or Class IIIa (under 5mW) for different market.
- 2. Input power can be fixed in 3 to 5 certain DC voltage.
- Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.

Caution: The cooper is internally connected to the circuit + pole, wrong connection may damage the laser module.

Model Number Definition:

LEM							
Ċ	liameter	total length	wavelength	output	lens	beam	angle
6	35:6.5mm	20:20mm	50:650nm	01:0.8mW	G:glass	P:point	
8	30:8.0mm	23:23mm	35:635nm	05:5mW	S:plastic	L:line	1:5°
1	0:10mm	27:27mm		10:10mW			2:20°
1	1:11mm	32:32mm		20:20mW			3:30°
1	2:11.5mm	35:35mm					6:60°
							$a \cdot a \cap o$

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage. Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.