

LEM Series Red Laser Point Module

Part No: LEM-5050-53xx-GP

Picture



Product Features

- High Stability and low noise
- Collimated or Adjustable focus beam
- Reverse Polarity Protection
- Custom Options Available

Application

- Measurement
- Optical Instrument
- Automation
- Alignment
- Point Mark

Specification

OPTICAL

Wavelength	532 nm
Optical Output Power ¹	<50mW or <30 mW or <20mW
Stability	<1%
Wavelength Drift	0.2nm/°C
Noise (20MHz Bandwidth)	<0.5% RMS
Laser Operation	Continuous
Laser Structure	DPSS from 808nm
Focus Lens	Glass Lens
Beam Divergence	<1.4mrad

ELECTRICAL

Operating Voltage ²	9 VDC
Operating Current	<600 mA
Control Circuit	Auto Power Control
Electrical Connections	+Red, -Black

MECHANICAL

Dimension	50x50x34mm
Cable ³	60mm
Operating Temperature	+20°C to +30°C
Storage Temperature	-40°C to +80°C

Notes

1. Please advise output power in advance.
2. AC 110/220 to DC adapter is standard.
3. Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.

Caution: The case is internally connected to the circuit, damage to the cooper surface may result in failure of the laser module.

Model Number Definition:

LEM- _____ - _____ - _____						
diameter	total length	wavelength	output	lens	beam	angle
65:6.5mm	20:20mm	50:650nm	01:0.8mW	G:glass	P:point	
80:8.0mm	23:23mm	35:635nm	05:5mW	S:plastic	L:line	1:5°
10:10mm	27:27mm	53:532nm	10:10mW			2:20°
11:11mm	32:32mm		20:20mW			3:30°
12:11.5mm	35:35mm					6:60°
						9:90°

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

Linda Enterprise Co., LTD

7F-3, No. 532, Sec. 1, Tai-Yuan Rd. Taichung Taiwan
 Tel: +886 4 22083300 Fax: +886 4 22083311
 www.linda-ent.com email:lindaent@ms25.hinet.net