


LEM Series Red Laser Point Module

Part No: LEM-8021-50xx-SP

Mechanical Drawing



Product Features

High Stability and low noise Collimated or Adjustable focus beam Reverse Polarity Protection Custom Options Available

Application

Measurement Optical Instrument Automation Alignment Point Mark

Specification

| OPTICAL | |
|-----------------------------------|-------------------------|
| Wavelength | 650 nm |
| Optical Output Power ¹ | <10mW or < 5 mW or <1mW |
| Stability | <1% |
| Wavelength Drift | 0.2nm/°C |
| Noise (20MHz Bandwidth) | <0.5% RMS |
| Laser Operation | Continuous |
| Laser Structure | Single Mode Laser |
| Focus Lens | PMMA Plastic lens |
| Beam Divergence | <18mrad |
| ELECTRICAL | |
| Operating Voltage ² | 3 or 4.5 VDC |
| Operating Current | <40 mA |
| Control Circuit | Auto Power Control |
| Electrical Connections | +Red, -Black |
| MECHANICAL | |
| Dimension | See chart |
| Cable ³ | 60mm |
| Operating Temperature | -10°C to +50°C |
| Storage Temperature | -40°C to +80°C |
| | |

Notes

- Please advise output power in advance, we can release Class II (under 1mW) or Class IIIa (under 5mW) or Class III (under 10mW) for different market.
- 2. Input power can be fixed in 3 to 5 certain DC voltage.
- 3. Standard cable length is 60mm, there are 100/150/200mm or with connector for your special need.
- Caution: The cooper is internally connected to the circuit + pole, wrong connection may damage the laser module.

Model Number Definition:



| diameter | total length | wavelength | output | lens | beam | angle |
|-----------|--|--|--|--|---|---|
| 65:6.5mm | 20:20mm | 50:650nm | 01:0.8mW | G:glass | P:point | |
| 80:8.0mm | 23:23mm | 35:635nm | 05:5mW | S:plastic | L:line | 1:5° |
| 10:10mm | 27:27mm | | 10:10mW | | | $2:20^{\circ}$ |
| 11:11mm | 32:32mm | | 20:20mW | | | 3:30° |
| 12:11.5mm | 35:35mm | | | | | $6:60^{\circ}$ |
| | | | | | | $9:90^{\circ}$ |
| | 65:6.5mm 80:8.0mm 10:10mm 11:11mm | diameter total length 65:6.5mm 20:20mm 80:8.0mm 23:23mm 10:10mm 27:27mm 11:11mm 32:32mm 12:11.5mm 35:35mm | 65:6.5mm 20:20mm 50:650nm 80:8.0mm 23:23mm 35:635nm 10:10mm 27:27mm 11:11mm 32:32mm | 80:8.0mm 23:23mm 35:635nm 05:5mW 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW | 65:6.5mm 20:20mm 50:650nm 01:0.8mW G:glass 80:8.0mm 23:23mm 35:635nm 05:5mW S:plastic 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW | 65:6.5mm 20:20mm 50:650nm 01:0.8mW G:glass P:point 80:8.0mm 23:23mm 35:635nm 05:5mW S:plastic L:line 10:10mm 27:27mm 10:10mW 11:11mm 32:32mm 20:20mW |

Operational Hazard-Semiconductor Laser Diode Module: This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage. Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.